











| | REV | BY | DATE | COMMENT | DIMENSIONS ARE IN INCHES TOLERANCES FRACTIONAL± TWO PLACE DECIMAL ± 0.03 THREE PLACE DECIMAL ± 0.010 UNLESS OTHERWISE NOTED | DRAWN | JMR | OINNOVATIVE COMPONENT | |
|--|------------------------------|-----|-------|---|---|------------------------|-----|-----------------------|----------------|
| | 0 | JMR | DRAFT | RELEASE DATE | | APPROVED | | | |
| | | 1 | | | | DATE | | PART NAME | |
| | | | | | | MIN. TORQUE N/A inlbs. | | | |
| | | | | | KNOB MATERIAL | | | | |
| | PROPRIETARY AND CONFIDENTIAL | | | | | | | | |
| OF INNOVATIVE COMPONENTS. ANY REPRODUCTION IN PART OR AS A | | | | OMPONENTS. ANY REPRODUCTION IN PART OR AS A | KNOB FINISH | INSERT MATERIAL | | K3A MASTER | DRAWING NUMBER |
| WHOLE WITHOUT THE WRITTEN PERMISSION OF INNOVATIVE COMPONENTS IS PROHIBITED. | | | | | INSERT PART NUMBER | INSERT FINIS | н | | K3 |
| | | | | | | 1 | | SCALE 1:1 | SHEET 1 OF 1 |